Primo SD

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Static dissipative pressed homogeneous vinyl flooring
Winder content	ISO 10581	Type I
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	**Norm**	**Tarkett Value**
Surface treatment		PUR Reinforced
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	3000 g/m²
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance #	EN 14041	0019-0047-DoP-2014-03
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 10.2kW/m²
Reaction to fire	AS/ISO 9239.1	Smoke 55%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m²•K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	**Norm**	**Tarkett Value**
Residual indentation	EN ISO 24343-1	≤ 0,10 mm Best measured value: 0,03 mm
Slip resistance	DIN 51130	R10
Slip Resistance	AS 4586	P3
Electrical Insulation	VDE0100, Part 600	Ri ≥ 5x10⁴Ohms
Electrical resistance	EN 1081	R1 < 10^8 Ω
Curl resultant to heat	EN ISO 23999	≤|8|mm for rolls ≤|2|mm for tiles
Castor chair	ISO 4918	Suitable
Light fastness	ISO 105-B02	≥ 7
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 %Average measured value : ≤ 0.25 % for tiles
Ease of Decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Seam Strength Average Value	EN 684	≥ 240 N/50mm
Seam Strength Individual Value	EN 684	≥ 180 N/50mm
Sustainability performances	**Norm**	**Tarkett Value**
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		4.81 kg CO_2eq /m²
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		3.78 kg CO_2eq /m²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 μg/m³)
Formaldehyde emission class		E1
Dimensions and designs		
Roll	Roll 2 x 23 m	
Number of designs available	8	

The above information is subject to modification for the benefit of further improvement (17/08/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
Suite 1, Level 3, 3 Columbia Court, Baulkham Hills NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au