


ProtectWall (1.5 mm)

Datasheet

Classification	Norm	ProtectWall 1.5
Product type	EN 259-1	Heavy Duty Wall Covering
Technical Characteristics	Norm	ProtectWall 1.5
Total thickness	EN ISO 24346	1,50 mm
Total weight	EN ISO 23997	2400 g/m ²
Wear layer thickness	EN ISO 24340	0,15 mm
Surface treatment		Top Clean XP
Installation method		Glue-Down
Performance for CE Marking	Norm	ProtectWall 1.5
Declaration of Performance #	EN 15102	0132-0065-DoP-2022-01
Reaction to fire	AS/NZ 3837	Group 1
	Average specific extinction area	131.1m ² /kg
Technical Performance	Norm	ProtectWall 1.5
Colour fastness to light	ISO 105-B02	≥ 6
Impact Resistance	EN 259-2	Resistant to impacts - No visible burst nor crack
Chemical resistance	ISO 26987	Not affected
Spongeability, washability, lyability, brushability	EN 12956	Super washable and brushable
Determination of Flexibility	ISO 24344 - EN 435	No damage, no crack
Seam Strength Average Value	EN 684	≥ 250 N/50mm
Bacteria Resistance	ISO 846 part A and C	Does not promote growth
Sustainability performances	Norm	ProtectWall 1.5
Vinyl Council Australia		PVC Best Practice
Recyclability through Resilooop		Recyclable
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m ³)
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs	Norm	ProtectWall 1.5
Roll		Roll 2 x 20 m
Number of designs available		23 (1.5)



For Global Green Tag certificates please see the Tarkett Australia page at globalgreentag.com

The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.