

Tapiflex Excellence (19dB)

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 11638	Polyvinyl chloride floor coverings with foam layer
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	42 General
Technical Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	3,25 mm
Wear layer thickness	ISO 24340	0,80 mm
Total weight	ISO 23997	3250 g/m ²
Surface treatment		TEKTANIUM ®
Installation method		Glue-Down
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-074-DoP-2024-01
Reaction to fire	A5/ISO 9239.1	Critical radiant flux 7.2kW/m ² Smoke 258%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN ISO 10456	0,04 m ² •K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,20 mm Average measured value: ca. 0,10 mm
Dimensional stability	EN ISO 23999	≤ 0.40 % Average measured value : ≤ 0.10 %
Impact sound reduction - ΔLw	EN ISO 717/2	19 dB
Reduction of in-room impact noise	NF S31-074	Class A (≤ 65 dB)
Slip resistance	DIN 51130 AS 4586	R10 P4
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Curl resultant to heat	EN ISO 23999	≤ 8 mm
Light fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recycled content		25 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		9.30 kg CO ₂ e/q /m ²
Total VOC Emissions (after 28 days)	EN 16516	Platinum (≤ 10 μg/m ³)
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		93



The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.