iQ Eminent

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous Vinyl floor covering
Binder content	ISO 10581	Type I
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	**Norm**	**Tarkett Value**
Surface treatment		New iQ PUR
Surface restoration		Yes
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	2750 g/m²
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance #	EN 14041	0019-0008-DoP-2013-07
Reaction to fire	AS/ISO 9239.1 AS/NZS 3837 (wall) Average specific extinction area	Critical radiant flux 11.0kW/m² Smoke 117%.min Group 3 238.8m²/kg
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m²•K/W
Technical Performance	**Norm**	**Tarkett Value**
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm Best measured value: 0,02 mm
Slip resistance	DIN 51130 AS 4586	R10 P4
Curl resultant to heat	EN ISO 23999	≤|8|mm for rolls
Clean room	ISO 14644-1	ISO class 4
Riboflavin Test	Fraunhofer method	Class 0 : Excellent
Castor chair	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 7
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.40 % for rolls
Ease of Decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Excellent Resistance
Bacteria resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability performances	**Norm**	**Tarkett Value**
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25.5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		3.48kg CO_2eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		1.81kg CO_2e /m² /year
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m³)
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		26

The above information is subject to modification for the benefit of further improvement (27/08/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
Suite 1, Level 3, 3 Columbia Court, Baulkham Hills NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au