iQ Megalit

Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous vinyl floor covering
Binder content	ISO 10581	Type I
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Technical Characteristics	**Norm**	**Tarkett Value**
Surface treatment		New iQ PUR
Total thickness	ISO 24346	2 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	2500 g/m²
Performance for CE Marking	**Norm**	**Tarkett Value**
Declaration of Performance #	EN 14041	0019-0001-DoP- 2013-07
Reaction to fire	AS/ISO 9239.1	Critical radiant flux 9.0kW/m² Smoke 288%.min
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance	EN 12667	~0,010 m²•K/W
Technical Performance	**Norm**	**Tarkett Value**
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm
Slip resistance	DIN 51130 AS 4586	R10 P4
Curl resultant to heat	EN ISO 23999	≤|8|mm for rolls
Clean room	ISO 14644-1	ISO class 3
Castor chair	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 7
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 % for rolls
Ease of Decontamination	ISO 8690 – DIN 25415	Excellent
Chemical resistance	ISO 26987	Excellent Resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability performances	**Norm**	**Tarkett Value**
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25.5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		3.48kg CO_2eq /m²
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		1.81kg CO_2e /m² /year
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m³)
Formaldehyde emission		E1
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		10



The above information is subject to modification for the benefit of further improvement (27/08/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website https://www.tarkett.com. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia
Suite 1, Level 3, Columbia Court, Baulkham Hills NSW 2153
(02) 8853 1200
customerservice@tarkett.com
www.tarkett.com.au

Tarkett