

# Surface Wall

## Datasheet

Classification	Norm	Tarkett Value
Product type	EN 259-1	Heavy Duty Wall Covering
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	2 mm
Total weight	EN ISO 23997	3400 g/m <sup>2</sup>
Wear layer thickness	EN ISO 24340	2 mm
Surface treatment		PU SHIELD
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 15102	0019-0065-DoP-2019-07
Reaction to fire	AS/NZ 3837 Average specific extinction area	Group 1 75.8m <sup>2</sup> /kg
Technical Performance	Norm	Tarkett Value
Colour fastness to light	ISO 105-B02	≥ 7
Chemical resistance	ISO 26987	Excellent Resistance
Sustainability performances	Norm	Tarkett Value
Vinyl Council Australia		PVC Best Practice
Recyclability through ReStart®		Recyclable
Recycled content		25,5 %
Total VOC Emissions	EN 16516	Platinum (≤ 10 µg/m <sup>3</sup> )
Formaldehyde emission class		E1
GreenTag		Level A
HealthRATE		Platinum
Dimensions and designs		
Roll		Roll 2 x 23 m
Number of designs available		7



For Global Green Tag certificates please see the Tarkett Australia page at [globalgreentag.com](https://globalgreentag.com)

The above information is subject to modification for the benefit of further improvement (24/11/2025). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com.au>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.

Tarkett Australia  
Suite 1, Level 3, Columbia Court, Baulkham Hills NSW 2153  
(02) 8853 1200  
[customerservice@tarkett.com](mailto:customerservice@tarkett.com)  
[www.tarkett.com.au](https://www.tarkett.com.au)

