Jacobsen®

Product Information Declaration

Audacity Detail Trims Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as **Audacity Detail Trims**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ ~~Exterior~~
✓ High Traffic	✗ ~~Low Traffic~~	✗ ~~Exposed Sunlight~~	✗ ~~Wet Areas~~
✗ ~~Antistatic Environment~~	✗ ~~Food Prep Areas~~	✗ ~~Clean Room~~	✓ With Wheels
✗ ~~Ramp/Entry~~	✓ Under Floor Heating	✗ ~~Over Existing Floor~~	

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	15 years Limited Residential, 5 years Limited Commercial
Residential	AC4
Commercial	AC4
Industrial	-

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CHF >11 kW/m2 (ISO 9239.1:2010)

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 0.5 mg/m3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code

V:280424

Product Information Declaration
Audacity Detail Trims Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Audacity Detail Trims** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration
Audacity Detail Trims Range

Identifiers

This JPID covers all colours from Audacity Detail Trims including:

T Mould Victorian Oak 2.4m 22064
T Mould Riverton 2.4m 22078
Square Nose Helena Bay 2.4m 22104
Square Nose Foxton 2.4m 22113
Square Nose Fiordland 2.4m 22119
Square Nose Eden 2.4m 22109
Square Nose Castlepoint 2.4m 22108
Square Nose American Oak 2.4m 22105
Reducer Victorian Oak 2.4m 22095
Reducer Riverton 2.4m 22103
Reducer Milford 2.4m 22102
Reducer Mercury Bay 2.4m 22099
Reducer Longwood 2.4m 22096
Reducer London Fog 2.4m 22100
Reducer Helena Bay 2.4m 22073
Reducer Foxton 2.4m 22101
T Mould Milford 2.4m 22077
T Mould Mercury Bay 2.4m 22085
T Mould Longwood 2.4m 22080
T Mould London Fog 2.4m 22086
T Mould Helena Bay 2.4m 22062
T Mould Foxton 2.4m 22076
T Mould Fiordland 2.4m 22081
T Mould Eden 2.4m 22084
T Mould Castlepoint 2.4m 22083
T Mould American Oak 2.4m 22063
Stair Nosing Victorian Oak 2.4m 22089
Stair Nosing Riverton 2.4m 22157
Stair Nosing Milford 2.4m 22156
Stair Nosing Mercury Bay 2.4m 22152
Reducer Fiordland 2.4m 22118
Reducer Eden 2.4m 22098
Reducer Castlepoint 2.4m 22097
Reducer American Oak 2.4m 22074
Quarter Round Victorian Oak 2.4m 22160
Quarter Round Riverton 2.4m 22172
Quarter Round Milford 2.4m 22170
Quarter Round Mercury Bay 2.4m 22167
Quarter Round Longwood 2.4m 22161
Quarter Round London Fog 2.4m 22168
Quarter Round Helena Bay 2.4m 22158
Quarter Round Foxton 2.4m 22169
Quarter Round Fiordland 2.4m 22176
Quarter Round Eden 2.4m 22166
Quarter Round Castlepoint 2.4m 22165
Stair Nosing Longwood 2.4m 22120
Stair Nosing London Fog 2.4m 22153
Stair Nosing Helena Bay 2.4m 22116
Stair Nosing Foxton 2.4m 22155
Stair Nosing Fiordland 2.4m 22175
Stair Nosing Eden 2.4m 22122
Stair Nosing Castlepoint 2.4m 22121
Stair Nosing American Oak 2.4m 22088
Square Nose Victorian Oak 2.4m 22106
Square Nose Riverton 2.4m 22115
Square Nose Milford 2.4m 22114
Square Nose Mercury Bay 2.4m 22111
Square Nose Longwood 2.4m 22107
Square Nose London Fog 2.4m 22112
Quarter Round American Oak 2.4m 22159

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	-
	Credit 21	-
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		-

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacoben.co.nz

NZBN:
9429040403328

Product Manufacturer: **China Floors**
Country of Origin: China

V:280424